



Certified to ISO
9001:2015
without design

50 Years of dedicated service

2998 Eastern Road • P.O. Box 1012 • Norton, Ohio 44203
(330) 825-4565 • Fax (330) 825-8699
WWW.ELSTONE.COM

THE FACTS

STONEKOTE®-6000-GREEN

CONFIDENTIALITY NOTICE: These documents contain confidential information belonging to the sender who is legally privileged. The information is intended only for the use of the individual or entity this is being sent to. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution or the taking of any action in reliance on the contents of this information is strictly prohibited.

DESCRIPTION:

STONEKOTE®-6000-Green is a durable fluoropolymer coating with good chemical resistance and outstanding non-stick properties. It has a maximum use temperature of 400°F, is completely color stable at elevated temperatures and may be postformed.

USES:

Heated sealing bars are notoriously troublesome. When coated with **STONEKOTE®-6000-Green**, sealing bars benefit from the coating's ability to repel the melted plastic while operating continuously at elevated temperatures.

Likewise, molds coated with **STONEKOTE®-6000-Green** are favored to produce a diversity of goods because of the coating's long lasting release properties.

FDA STATUS:

This product does conform with regulations governing use for direct food contact.

Guarantee of performance of applied coatings by E. L. Stone Company are neither implied nor expressed. E. L. Stone Company has no control over the myriad of possible service conditions (chemicals, temperatures, mixtures, etc.) E.L. Stone Company recommends that a test sample first be evaluated by the customer under conditions as close as possible to their intended service condition.

® REGISTERED SERVICE MARK OF E.L. STONE COMPANY, INC.