



Certified to ISO
9001:2015,
without design

50 Years of dedicated service

2998 Eastern Road • P.O. Box 1012 • Norton, Ohio 44203
(330) 825-4565 • Fax (330) 825-8699
WWW.ELSTONE.COM

THE FACTS

STONEKOTE®-2000-Dark Green

CONFIDENTIALITY NOTICE: These documents contain confidential information belonging to the sender who is legally privileged. The information is intended only for the use of the individual or entity this is being sent to. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution or the taking of any action in reliance on the contents of this information is strictly prohibited.

DESCRIPTION:

STONEKOTE®-2000 is a non-stick, self-lubricating finish based on a special fluorocarbon resin and reinforced fillers. The coating provides desirable hardness and abrasion resistance. After curing, a fluorocarbon rich surface is formed which provides non-stick and low friction properties. This product provides increased abrasion resistance with thinner film builds.

USES:

The toughness and resiliency of this product, plus its good non-stick and low coefficient of friction make it suitable for uses where other non-sticks are not appropriate due to insufficient hardness or wear life. Some typical examples are saw blades, wood drill bits, mold release, aircraft tooling and low load-bearing surfaces. Coefficient of friction is approximately .08 - .1 (kinetic).

Guarantee of performance of applied coatings by E. L. Stone Company are neither implied nor expressed. E.L. Stone Company has no control over the myriad of possible service conditions (chemicals, temperatures, mixtures, etc.) E. L. Stone Company recommends that a test sample first be evaluated by the customer under conditions as close as possible to their intended service condition.

® REGISTERED SERVICE MARK OF E.L. STONE COMPANY, INC.