



Certified to ISO
9001:2015,
without design

2998 Eastern Road • P.O. Box 1012 • Norton, Ohio 44203
(330) 825-4565 • Fax (330) 825-8699
WWW.ELSTONE.COM

THE FACTS

STONEKOTE®-60-Clear or BLACK

CONFIDENTIALITY NOTICE: These documents contain confidential information belonging to the sender who is legally privileged. The information is intended only for the use of the individual or entity this is being sent to. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution or the taking of any action in reliance on the contents of this information is strictly prohibited.

DESCRIPTION:

STONEKOTE®-60 is E.L. Stone's newest offering for extreme chemical applications where release and corrosion resistance are needed.

USES:

STONEKOTE®-60 is recommended for those projects which require excellent chemical resistance and long-lasting abrasion resistance. It also has excellent properties for thermal and electrical insulation. It can be applied in thickness ranging from .003"-.015", and even thicker in extreme applications. It can be used continuously at 300°F

FDA STATUS:

STONEKOTE®-60 conforms with regulations governing use for direct food contact.

Guarantee of performance of applied coatings by E. L. Stone Company are neither implied nor expressed. E. L. Stone Company has no control over the myriad of possible service conditions (chemicals, temperatures, mixtures, etc.) E. L. Stone Company recommends that a test sample first be evaluated by the customer under conditions as close as possible to their intended service condition.

® REGISTERED SERVICE MARK OF E.L. STONE COMPANY, INC.