



Certified to ISO
9001:2015,
without design

2998 Eastern Road • P.O. Box 1012 • Norton, Ohio 44203
(330) 825-4565 • Fax (330) 825-8699
WWW.ELSTONE.COM

THE FACTS

STONEKOTE®-72-BLACK

CONFIDENTIALITY NOTICE: These documents contain confidential information belonging to the sender who is legally privileged. The information is intended only for the use of the individual or entity this is being sent to. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution or the taking of any action in reliance on the contents of this information is strictly prohibited.

DESCRIPTION:

STONEKOTE®-72-Black is a unique, high release, high-wear and scratch resistant coating.

STONEKOTE®-72-Black, a second generation coating, is internally reinforced with a special blend of diverse ceramic materials. It has outstanding adhesion and a smooth, glossy finish. In addition, this system has superb abrasion resistance and outstanding nonstick performance.

USES:

STONEKOTE®-72-Black is designed for surfaces, which require nonstick properties and are subjected to high wear and/or abrasives.

FDA STATUS:

This product conforms with regulations governing use for direct food contact.

Guarantee of performance of applied coatings by E.L. Stone Company are neither implied nor expressed. E.L. Stone Company has no control over the myriad of possible service conditions (chemicals, temperatures, mixtures, etc.) E.L. Stone Company recommends that a test sample first be evaluated by the customer under conditions as close as possible to their intended service condition.

® REGISTERED SERVICE MARK OF E.L. STONE COMPANY, INC.